



Weighing Platforms 2880-2882, 2884

Sturdy and extra flat design with high reserves in the load capacity

Dual range weighing platform: Division of the weighing capacity in two ranges. The first part of the weighing range has a finer graduation. Thus the scale is more accurate.

Platforms

 The weighing platforms 2880, 2881, 2882 and 2884 can be used for weighing, counting and checking and can be connected to the Soehnle indicators 2760, 2761 or 2780. Please see separate indicator leaflets for detailed information.

Specifications

- Sturdy construction with one load cell made of anodised aluminium alloy protection class IP 65
- Mechanical overload security device to protect the load cell
- Easy determination of weight

- Platform cover of all models are made of stainless steel
- 2880 and 2881: The base is made of water resistant aluminium alloy. Excellent rust protection. Suitable for operation in humid environments.
- 2882 and 2884: The supporting structure is made of painted steel. Not suitable for humid environment.
- Length of the connection cable between the weighing platform and the indicator is 2 m
- Readout in kg or lb

Optional

Stand for the indicator, made of aluminium alloy. To be fixed to the platform, height 500 mm. for model 2880: Order no. 2504.06.001 for model 2881: Order no. 2504.04.001 for model 2882: Order no. 2504.05.001 Stainless steel underframe with 2 rolls. Height 500 mm, dimension 680 x 730 mm. Order no. 2502.01.001

Officially stamped

The weighing platforms are approved on the basis of the norms of the European Community according to verification class III.

SOEHNLE plug-in reference module After changing the indicator no new verification necessary because the verification data are stored in the

(6



plug-in reference module.





Туре	Order no.	Platform size mm	Weighing range kg	Increments	weight kg
2880	2880.05.001	310 x 275 x 80	3	up to 1,5 kg = 0,5 g from 1,5 kg = 1 g	6
	2880.06,001	310 x 275 x 80	6	up to 3 kg = 1 g from 3 kg = 2 g	
	2880.12.001	310 x 275 x 80	15	up to 6 kg = 2 g from 6 kg = 5 g	
	2880.13.001	310 x 275 x 80	30	up to 15 kg = 5 g from 15 kg = 10 g	
	2880.14.001	310 x 275 x 80	60	up to 30 kg = 10 g from 30 kg = 20 g	
2881	2881.13.001	520 x 400 x 85	30	up to 15 kg = 5 g from 15 kg = 10 g	16
	2881.14.001	520 x 400 x 85	60	up to 30 kg = 10 g from 30 kg = 20 g	
	2881.15,001	520 x 400 x 85	150	up to 60 kg = 20 g from 60 kg = 50 g	
7882	2882.44.001	660 x 550 x 125	60	up to 30 kg = 10 g from 30 kg = 20 g	52
	2882.45.001	660 x 550 x 125	150	up to 60 kg = 20 g from 60 kg = 50 g	
	2882.46.001	660 x 550 x 125	300	up to 150 kg = 50 g from 150 kg = 100 g	
2884	2884.45.001	800 x 600 x 125	150	up to 60 kg = 20 g from 60 kg = 50 g	52
	2884.46.001	800 x 600 x 125	300	up to 150 kg = 50 g from 150 kg =100 g	

Please note our stainless steel weighing platforms for especially wet employments also.

Your specialist dealer:

